



ROCLAND

High performance topping

The factors affecting abrasion resistance of concrete are well known. **Cement quality, mineral composition, curing and water/cement ratio at the surface are among the most important factors.**

The visual appearance of the floor is dependent upon the ease of finishing, consistency of colour and a surface free from crazing and other imperfections

Rocland dry-shake pre-mixed hardeners have been improved recently using the latest technology in cement and additives.

These improvements have been achieved principally in:

- Cement content and strength classes
- The use of a shrinkage reducing admixture combined with a water reducing plasticiser
- The use of new **generation pigments** and mineral fillers
- Workability aids

The results of this **unique** factory blending are :

- Less surface crazing and cracks
- Uniformed setting time - **leading to improved quality of finish**
- Reduced porosity and increased abrasion resistance
- Better colours, **easier cleaning**

Where to use **ROCLAND HP TOPPING**S?

Rocland Hp Toppings are designed for :

- Flat and superflat floors in logistics and industrial facilities
- **Cash & Carry Warehouses**
- DIY and retails markets
- **Museums, Art Galleries and other public places**

The formulation of the product has been specially developed to enable use with self-compacting concrete floors.

ROCLAND HP TOPPINGS should always be cured using specially formulated compatible spray applied curing membranes

Note :

Whilst all reasonable care is taken in compiling technical data on the company's products, all recommendations or suggestions regarding the use of such products are made without guarantee since the conditions of use are beyond the control of the company. It is the customer's responsibility to satisfy himself that each product is fit for the purpose for which he intends to use it and that the actual conditions of use are suitable.



Z.A. Les Monts du Matin
Rue des Lauriers
F-26730 La Baume d'Hostun
France
Office phone : + 33 4 75 48 37 50

www.rocland.eu
contact@rocland.eu